



## 8mm Remington Magnum

.323"	8mm Semi-Spitzer SP Hot-Cor®
Weight (grains)	170
Ballistic Coefficient	0.311
Sectional Density	0.233
COAL Tested	3.575"
Speer Part No.	2283

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Remington	CCI 250	72.0	2995	<b>76.8</b>	3172
Alliant Reloder 16	Remington	CCI 250	73.0	3007	<b>77.4</b>	3159
IMR 4831	Remington	CCI 250	74.0	2865	<b>80.0</b>	3114
IMR 4350	Remington	CCI 250	73.0	2902	<b>77.0</b>	3078
Hodgdon H380	Remington	CCI 250	67.0	2828	<b>71.0</b>	3000
Hodgdon H414	Remington	CCI 250	69.0	2817	<b>73.0</b>	2970
Winchester 760	Remington	CCI 250	70.0	2795	<b>74.0</b>	2965
IMR 4064	Remington	CCI 250	62.0	2761	<b>66.0</b>	2940
IMR 4895	Remington	CCI 250	59.0	2740	<b>63.0</b>	2919

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*