



## 8mm Remington Magnum

<b>0.323</b>	<b>8mm Spitzer SP Hot- Cor®</b>
<b>Weight (grains)</b>	200
<b>Ballistic Coefficient</b>	0.440
<b>Sectional Density</b>	0.274
<b>COAL Tested</b>	3.575"
<b>Speer Part No.</b>	2285

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Remington	CCI 250	72.0	2763	<b>78.0</b>	2996
Alliant Power Pro 4000-MR	Remington	CCI 250	75.0	2870	<b>78.6</b>	2993
Alliant Reloder 17	Remington	CCI 250	69.5	2831	<b>74.5</b>	2985
IMR 7828	Remington	CCI 250	79.0	2712	<b>83.0 C</b>	2938
IMR 4350	Remington	CCI 250	70.0	2770	<b>74.0</b>	2936
Alliant Reloder 16	Remington	CCI 250	70.0	2813	<b>73.0</b>	2911
IMR 4064	Remington	CCI 250	60.0	2638	<b>64.0</b>	2803
IMR 4895	Remington	CCI 250	57.0	2564	<b>61.0</b>	2736
IMR 3031	Remington	CCI 250	57.0	2561	<b>61.0</b>	2732
IMR 4320	Remington	CCI 250	58.0	2544	<b>62.0</b>	2717

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*